

SUMMARY OF THE PRESENT INVENTION

Thus, this invention [offers] provides a corner cutter [that is characterized as being] [constructed] having [by] upper and lower blades [being respectively established such as] with the upper and lower blade edge lines [of the same upper and lower blades] mutually opposing [(each other[])] on [the upper and lower blade edge section of] a cutter main body in [an almost] a scissor-like shape [such] with[as] the opening and closing motion of the upper and lower blades cutting the plate glass.

Further, the same upper and lower blade edge lines [almost] substantially coincide [to] at a planned cut line of [a] the plate glass corner section.

Also, [there are] the following characteristics are added.

At least one end section of the upper and lower blade edge lines of the [same] upper and lower blades are [constructed such as obtaining] disposed to provide a position outside the plate glass in a condition where the upper and lower blades are closed.

The space between the end sections of the upper and lower blade edge lines is narrower than the space between the center section of the [same] upper and lower blade edge lines [in a condition where] when the upper and lower blades are closed.

The center section of the [above-mentioned] upper and lower blade edge lines curves outwardly [to] toward the cutter body side[.

The center section of the above-mentioned upper and lower blade edge lines curves to] and toward the reverse side of the cutter body.

[Here, sheet form] The sheets of brittle materials are [materials that are brittle and in a sheet] in the form [such as] of plate glass, mirrors,[(bathroom)] tiles and [(roof)] tiles.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a lateral view of a corner cutter pertaining to a first embodiment of the present invention.

Figure 2 is a plan view thereof.

Figure 3 is a front view thereof.

Figure 4 is a partial cross-sectional lateral view of the upper and lower blades of the first embodiment.

Figure 5 is a partial plan view showing utilization of a corner cutter of the first embodiment.

Figure 6 is a front view showing utilization of a corner cutter of the first embodiment.

Figure 7 is a partial plan view of a corner section of the first embodiment.

Figure 8 is a partial lateral view of a corner cutter pertaining to a second embodiment of the present invention.

Figure 9 is a partial plan view thereof.

Figure 10 is a front view thereof.

Figure 11 is a partial plan view showing utilization of a corner cutter of the second embodiment.

Figure 12 is a partial lateral view showing utilization of a corner cutter of the second embodiment.

Figure 13 is a partial plan view of a corner section of the second embodiment.

Figure 14 is a lateral view of a guide of the present invention.

Figure 15 is a plan view of the guide of the present invention.

Figure 16 is a front view of the guide of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

An actual embodiment of the invention is as follows.

Upper and lower blades which open and close and are mutually opposing [(each other)] are established on a blade edge section of a cutter body that is formed in a[n almost] scissor-like shape[.]. The upper and lower blade edge lines of the [above-mentioned] upper and lower blades [almost] substantially coincide [to] at a planned cut line of the plate glass, and the plate glass [is such as that which] is cut out [being] along [a] the planned cut line.

Further, the upper and lower blade edge line is longer than the [above-mentioned] planned cut line and both edges of the [same] upper and lower blade edge line [are such as obtaining] provide a position outside the plate glass[; and,]. [t]The space between opposite [both] end sections of the upper and lower blade edge lines [of the same upper and lower blades] is narrower than the space [(between)] the center sections of the [same] upper and lower blade edge lines[;]. [d]During the cutting operation, the distribution of the clamping pressure of the upper and lower blades [to] on the plate glass is the greatest at the plate glass edge and gradually lessens relative [to the approach] to the center section[.]. [and] [t]The crack that is produced at the plate glass edge [is such as] run[ning]s toward the center section along the upper and lower blade edge lines.

Examples

Actual examples of the invention are explained by referring to the Figures.

FIGS. 1-6 show [the] a first [E]xample of a corner cutter A1 [pertaining to] of the present

invention. This corner cutter A1 [is one for] shap[ing]es a corner section 2 of a sheet [form] of brittle material, such as plate glass 1, into an almost [1/4] one quarter arch shape with the center section curving [to the inside] outwardly as shown in FIG. 7. The right handle section 3 and [lower] upper blade edge section [6] 5 are formed as one unit and the left handle section 4 and [upper] lower blade edge section [5] 6 are formed as [one] another unit [and (these units)] which are pivotally attached to swing freely by means of pivot 7. A[n almost] scissor-like shaped cutter body 8 is formed and the upper and lower blades 9, 10, which are formed from ultra-hard metal alloys, are set in upper and lower blade edge sections 5, 6. In the Figures, 11 [is] are [a] handle section covers, 12 is a return spring, and 13 is a stop that maintains cutter body 8 in an open condition.

The upper and lower blade edge lines 14, 15 of upper and lower blades 9, 10 are formed in a[n almost 1/4] substantially one quarter arc shape and the center sections curve to the side of cutter body 8[side], as shown in the plan [figures] views of FIG. 2 and FIG. 5 and[,] are formed [such as] to coincid[ing]e with the [below-mentioned] planned cut line C1 of Fig. 7. Further, the space d1 of the upper and lower blade edge lines 14, 15[(]between[)] the left and right [two] edges is narrower than the space d2 [(]between[)] the center sections of the upper and lower blade edge lines 14, 15 in the condition where the upper and lower blades are closed, as shown in the front view of FIG. 3. Also, the upper and lower blade edge lines 14, 15 of the upper and lower blades 9, 10 edges are exactly opposite, as shown in the cross-sectional diagram of FIG. 4, and the plate glass 1 receives clamping pressure between the upper and lower blade edge lines 14, 15 by the opening and closing of the upper and lower blade edge sections 5, 6[; t]. The outside surface 16

of the upper and lower blades 9, 10 is formed to be perpendicular to plate glass 1, which is the object to be cut, and only the inside surface [only] is formed as a single [(]blade[)] edge with a rake or angle α .

The [utilization] method of using a corner cutter A1 of the first Example is as [in the] follow[ing]s.

Planned cut line C1 is set by establishing the outside grinding material m shown in Fig 7, of the [same] planned finish line B1, by marking off [planned finish] line B1 on a corner section 2 of plate glass 1 as shown in FIG.5. The upper and lower blade edge lines 14, 15 conform[s] to the [same] planned cutting line C1, and both the right and left [both] edge sections of the [same] upper and lower blade edge lines 14, 15 are positioned outside the edge of plate glass 1. When upper and lower blade edge sections 5, 6 are closed by squeezing the right and left handles 4, 3, as shown in FIG.6, the plate glass 1 is clamped between upper and lower blade edge lines 14, 15. But, as [in the] aforementioned, clamping pressure is produced in both directions where crossing orthogonally at the surface of plate glass 1 between the [same] upper and lower blade edge lines 14,15 [since the upper and lower blade edge lines 14,15] which are exactly opposite and the distribution of the clamping pressure is greatest at both edge sections of [the plate glass 1] planned cut line C1 and gradually decreases relative to approaching the center section.

The crack which is produced in plate glass 1 is first produced at both edge sections of the planned cut line C1 [of the plate glass 1] periphery where the clamping pressure is the greatest, then

moves from that toward the center section of [planned] cut line C1, and divergences from [planned] cut line C1 are prevented by controlling the clamping pressure of the upper and lower blades 9, 10.

Further, a section outside planned cutting line C1 is crushed since a rake a, shown in Fig. 4, is formed only at the inside surface of upper [and lower] blade[s] 9 which engages an opposing surface of lower blade 10. The original form is maintained for the section inside planned cut line C1 and the forming of a corner section 2 in [planned] cut line C1 as shown in FIG. 7 is possible, since a crack along [planned] cut line C1 is produced in front of where this crushing occurs and crushing proceeding to inside beyond the same crack is prevented.

After the cutting operation is performed, the corner section 2 is ground and finished [with performance] to planned finish line B1 with items like a grinder or whetstone.

FIGS. 8-12 show a second example of a corner cutter A2 [of a second Example; t]. The corner section 2 of plate glass 1 shown in Fig. 13 is one that is cut along a planned finish line B2 of [an almost 1/4] about a one quarter arch shape with a center section that curves [to the inside as shown in FIG. 13;] inwardly. [p]Planned cut line C2 establishes the grinding material [m] from [the above-mentioned] planned finish line B2, and is shaped in [an almost 1/4] the one quarter arch shape with the center section curved [to the inside] inwardly.

[Concretely, u]Upper and lower blades 22, 23 curve in [an almost 1/4] about a one quarter arch shape outside the center section for upper and lower blade edge sections 20, 21 of cutter body 8 that

is formed [almost] substantially in the same way as the aforementioned first Example[; o]. One of the end sections of the [same] upper and lower blades 22, 23 is parallel with the length of cutter body 8 and the other end section is positioned [such as] orthogonally [crossing this]to the length.

[Further, t]The [above-mentioned] upper and lower blades 22, 23 are also mutually exactly opposite the upper and lower blade edge lines 24, 25 in the same way as the first [E]example, and the space between the upper and lower blade edge lines 24, 25 of the end sections of the side that is parallel to the length of the cutter body 8 is narrower than the space at the other end. Further, the rakes or angles of the upper and lower blades 22, 23 are also [established at] only on the cutting side [where there is cutting] in the same way as the first [E]example.

FIGS. 11 and 12 show [utilization] conditions for use of [a] the second [E]example corner cutter A2. The end section of the side that is parallel to the length of the cutter body 8 of the upper and lower blade edge lines 24, 25 is positioned [outside] alongside one edge of corner section 2 of plate glass 1 [with] which forms a right angle [formed; t]. The other end is positioned near the other edge of corner section 2. First, a crack is produced in a position where the edge of the plate glass [I] 1 and the upper and lower blade edge lines 24, 25 cross[, t]. This crack runs toward the other end section of the upper and lower blade edge lines 24, 25, and cutting of plate glass 1 along planned cut line C[I]2 is possible when upper and lower blade edge sections 20, 21 are closed by squeezing the right and left handle sections 4, 3 as with the first example of Fig. 1.

Further, the end section of the side that does not cross with the plate glass 1 edge of [the aforementioned] upper and lower blade end lines 24, 25 does not contact the other edge of plate glass 1, and a force which separates the cut-off section outside planned cut line C2 is produced due to the rake [which is] or angle established on upper and lower blades 22, 23. This force directs the crack in the direction of the [above-mentioned] other edge and the crack is prevented from running toward the inside of planned finishing line B2.

FIGS. 14-16 show a guide 30 mounted on corner cutter A1 of the first example for [the simplification position determination] simplifying the positioning of corner cutter A1 [to] on plate glass 1 [by being installed on a corner cutter A1 of the first Actual Example]. Setting section 33 extends from [the] a right angle [peak] end section 32 of the [almost] approximately right-angle isosceles triangle shaped bottom plate 31 in the direction of the cutter [blade] body 8 and the periphery of the [2] two sides which [clamp] secure the [peak] end position. [t]The respective right and left guide plates 34, 35 [which] are [situated] disposed on the right and left periphery of [the] setting section 33 for [the same] guide 30[;], and[,] position determining hole 36 and screw insertion hole 37 are formed in setting section 33.

Further, position determining projection 38 and hidden female screw hole 39 are formed on the outside surface of the lower blade edge section 6 of cutter body 8[; p]. Position determining projection 38 fits through position determining hole 36 of setting section 33 [such as] with guide 30 being [established] fastened on corner cutter A1 by means of [a] wing nut 40 which fastens [screws together and contracts] onto a screw through female screw hole 39 [by insertion through screw

insertion hole 37].

Thus, the right angle corner section 2 of plate glass 1 [with a right angle formed] is inserted between the right and left guide plates 34, 35[, w]. When the periphery of that [same] plate glass 1 abuts [to] the inside surface of the right and left guide plates 34, 35, the position of the upper and lower blade edge sections 5, 6 of corner cutter A1 is correct [and]. E[e]fficient corner treatment operation can then be performed [which does not require things like] without requiring marking-off, since [(]that[)] can be easily determined.

Further, [a] the corner cutter of this invention is not limited to the above-mentioned cutting of plate glass, but can be widely utilized for materials that are in a sheet form and are brittle such as mirrors, [(]bathroom[)] tiles and [(]roof[)] tiles.

Effects such as the following can be obtained by the present invention.

The invention [as described in Claim 1 is constructed such as] utilizes the opening and closing motions of upper and lower blades to result in cutting of plate glass due to the [respective upper and lower blades being established such as the] upper and lower blade edge lines [of the same upper and lower blades] mutually opposing [(]each other[)] in [the upper and lower blade edge section of] a cutter body that is formed in a[n almost] scissor-like shape[;]. Further, a corner section of plate glass can be cut on a planned cut line by one opening and closing operation of the upper and lower blade edge sections and the efficiency of corner section treatment operations can be improved since the

[same] upper and lower blade edge lines [almost] substantially coincide at a planned cut line of a corner section of plate glass.

The invention [as described in Claim 2] can produce a crack with little clamping pressure by restricting the origin of a crack that is produced by the clamping pressure of the upper and lower blades to the plate glass periphery when a corner section is cut.[since the construction is such as] This results from positioning at least one end section of the upper and lower blade edge lines at the periphery of [the same upper and lower blades beyond] the plate glass [in a condition where] when the upper and lower blades are closed.

The invention [as described in Claim 3] has the distribution of the clamping pressure to the plate glass being greatest at the end sections with the space of the upper and lower blade edge line being narrow and the direction in which the crack runs can be controlled while the crack can be prevented from going beyond the planned cut line,[since the space between the center sections of the upper and lower blade edge lines is narrower than the same upper and lower blade edge line center section in a condition where the upper and lower blades are closed.]

The invention [as described in Claim 4 has] provides the simple shaping of a corner section [with a center section] curving to the outside [since] and the center sections of the [above-mentioned] upper and lower blade edge lines curve to the cutter body side.

The invention [as described in Claim 5 has] also provides the simple formation of a corner section [with the curved section] curving to the inside [since] and the center sections of the [above-

mentioned] upper and lower blade edge lines curve to the reverse side of the cutter body.

[Explanation of the Symbols

A1-corner cutter

A2-corner cutter

1-plate glass (sheet form brittle material)

2-corner section

5, 6-upper and lower blade edge sections

8-cutter body

9,10- upper and lower blades

14, 15- upper and lower blade edge lines

C1-planned cut line]

It will be understood that the embodiments described herein are merely exemplary and that a person skilled in the art may make many variations and modifications without departing from the sphere and scope of the invention. All such variations and modifications are intended to be included in the scope of the invention as defined in the appended claims.